

Idaho National Engineering and Environmental Laboratory

Deactivation and Decommissioning Focus Area, Ohio Field Office, Fernald Environmental Management Project, Fernald Ohio

# An Integrated Excavation Control System

Robert Janke (DOE- FEMP) Michael Carpenter (INEEL)

March 6th, 2002





# What is Integrated Excavation Control System (IECS)?

- A suite of real-time technologies used to manage nearsimultaneous characterization of excavation activity at Fernald's Production Area and Waste Pit Area
- IECS real-time systems consist of hardware, sensor, software, and positioning technology
- Two primary technologies are:
  - Excavation Monitoring System (engineered and built by INEEL)
  - Gator



#### **Excavation Monitoring System Description**

EMS is of modular construction









System is a self-contained gamma-detection system that

scans excavation floor







Deployed from standard tracked-excavator boom





Excavator <u>operator</u> is guided by visual display of operating

conditions:

detector speed

- proximity to surface
- proximity to trench sidewalls
- Display provides visual and collision-avoidance alarms for operator





- Platform assembly houses system integration package:
  - Excavator-to-platform coupler
  - Onboard computer

GPS receiver and antenna (positioning)



Alternative Laser tracking system (localized positioning)



- System controlled from remote van workstation
- System integrates:
  - EMS platform functions
  - excavator operator monitor and alarm system
  - data analysis software
  - real-time mapping/display
  - data validation



#### IECS Survey-grade GPS technology

- Survey-grade GPS technology deployed on current large-area-scanning platform: "Gator"
- Will be applied to the problem of rapid and accurate estimation of excavation volumes





#### IECS Survey-grade GPS technology (cont.)

- Survey-grade GPS units were tested along with the EMS during the testing periods in June and December 2001
- Work has been done to develop topographical mapping capabilities using the GPS systems on Gator all-terrain vehicle
- Capability extended to calculation of excavated soil volumes on basis of topographic data
- Mapping and volume estimating capability integrated into the real-time radiological characterization process as part of the IECS



#### FEMP IECS Goals

- Fernald to begin Production Area remediation phase involving Integrated Excavation Control System (IECS) technology in Spring FY-2002
- Characterize soils in at-or-below-grade portions of structures within Production Area
- IECS utilize real-time characterization of large-area soil areas cleanup at Fernald to:
  - reduce human exposure to health risks
  - reduce remediation operating costs
  - accelerate cleanup process where possible



#### FEMP IECS Goals (cont.)

 Expand and enhance the FEMP's capabilities for insitu measurement of radionuclide concentrations in soils

 Allow estimates of excavated soil volumes to be made rapidly, and

Minimize radioactive wastes generated during soil excavation



#### IECS Technical Approach

- IECS technology, Excavation Monitoring System (EMS), will be deployed in Production Area to perform Excavation Control Surveys (ECS) for OSDF above-WAC soils
- As surface soil is removed, freshly exposed soil is scanned with the EMS







#### IECS Technical Approach (cont.)

- EMS utilizes Nal detector to scan survey area to determine spatial extent of contamination and detect and delineate areas of activity above WAC in real-time (for transfer to On-Site Storage Facility
- Hotspot characterization performed using Nal/HPGe detectors
- Waste Acceptance Criteria (WAC) volume of soil requiring disposal (~38,000yd³) reduced by 20% using IECS approach
- Approach requires that EMS provide:
  - location
  - spatial extent
  - concentrations of contaminants



#### Technical Approach (cont.)

- Integrated Excavation Control System (IECS) concept addresses Fernald Production and Waste Pit Areas needs to enhance management of at-or-below grade D&D structure removal and associated soils remediation
- With acquisition of the real-time in situ measurement technology, FEMP replaces baseline "representative" sampling techniques that require human interaction with potentially high hazard risk environments associated with excavation of foundations, pits and trenches.



#### **Primary Contaminants of Concern**

 Efficiently characterize Primary Contaminants of Concern (COC) that account for 90% of the health risk from soil at the site are (Source, Site Excavation Plan, 1997):

| COC             | Free Release Levels (FRLs) |  |
|-----------------|----------------------------|--|
| – total uranium | 82 ppm                     |  |
| - thorium-232   | 1.5 pCi/g                  |  |
| – radium-226    | 1.7 pCi/g                  |  |
| – radium-228    | 1.8 pCi/g                  |  |
| - thorium-228   | 1.7pCi/g                   |  |
|                 |                            |  |



#### Technical Maturity of IECS

- Both EMS and Gator are significantly improved prototype systems
- EMS predecessor called Warthog (EM-50 funded development). Gator and RTRAK originated mobile, Nalbased scanning at the FEMP
- Warthog demonstrated at MEMP, FEMP, UKAEA
- RTRAK originally used at Rocky Flats for large area soil scanning
- Scanning systems have matured to "robust" field systems



#### Technology/Project Support

- No system can be "taken out of the carton" and utilized without a baseline of technical support
- FEMP has developed a comprehensive, dedicated support team made up of FEMP, INEEL, ANL, and EML expertise
- Dedicated FEMP support structure ensures continuity in project cost-saving and risk reduction goals
- Thrust 1 outlines "multi-disciplinary, hands-on, committed" team concept which <u>already</u> exists at FEMP
- Continued execution of Thrust 1 priorities at FEMP require only financial underpinning, process already in place



#### Technology/Project Support (cont.)

- FEMP is in the process of realizing a 10:1 ROI for the deployment of the "Integrated Technology Suite for Cost-Effectively Delineating Contamination in Support of Remedial Actions" to reduce High Risk/High Cost baseline strategies at Fernald (Thrust 2)
- An "aggressive investment strategy" is logical given that FEMP has an effective and measurable process in place; where additional funds are specifically and efficiently targeted at relatively low-risk/high payoff outcomes



#### Meeting Schedule Requirements (cleanup by 2006)

- To date development of IECS technology has occurred on time and budget to meet accelerated baseline schedule requirements for soils and Production Area remediation activity
- EMS will be used in Production Area in Spring 2002 remediation activities as primary IECS tool



#### **Benefits**

- Estimated cost savings using IECS: \$5,400K
- Dramatically reduces or eliminates human interaction with potentially high hazard risk environments
- Baseline sampling technique would require physical samples be taken during field screening -these are eliminated
- Construction safety issues, i.e. excavation slopes, fall hazards etc., are significantly reduced by removing RCT personnel from excavation settings



#### Benefits (cont.)

- Technology Safety Data Sheet will be available in Spring 2002
- OSHA requirements were considered in EMS design:
  - lightweight modules
  - elimination of electrical shock hazard
  - ease of use
- Use of IECS creates no secondary waste stream



#### Benefits (cont.)

- FEMP is supported by a diverse team from INEEL, EML, ANL where elapsed time from defining design requirements to field deployment are separated by few months and few dollars (Thrust 1)
- Technical support from team contributors is not subordinated to external factors such a local site deliverables
- IECS technology brought from prototype to field ready status at relatively low cost and in a few months where risk to High Risk/High Cost Baselines have been significantly reduced or eliminated (Thrust 2)
- IECS has become new baseline technology



#### Technical Progress

- IECS EMS requirements finalized January 2001, system delivered to FEMP site (from INEEL) in June 2001
- EMS acceptance trials were successful, identified minor modifications to EMS and system software executables
- Completed necessary regulatory documentation and Operator's manuals
- Conducted real-time technology demonstration at Oak Ridge during the week of July 9, 2001 for the benefit of the site contractor, involved regulators, and other stakeholders



EMS acceptance trials June 2001









- Assembled ASTD partners for final acceptance testing and system calibration of the EMS during the week of December 3, 2001
- Prepared a draft First Year Summary Report for the IECS
- Technical results enable FEMP to continue soils clean-up in Production Area on schedule while exemplifying content of both Thrusts by having the technology, support team, desired risk levels, converted baseline and high quality attributes already in place



 Calibration of EMS with detectors on FEMP calibration pad in December 2001





- Interest has been expressed by MEMP to utilize a variant of the system in the near future
- Private industry has expressed interest in nonradioactive application of the system in construction settings
- A private industry concern has expressed interest in intellectual property for potential system variations, enhancements etc.